Synthetic Slings – Webbing & Round

Working Load Limits In Tonnes

CERTEX
Lifting Products and Services

		Straight Lift	Choked Straight Lift	Parallel Basket	Basket Hitch, Direct Loaded or 2, 3 and 4 leg Slings			Choke Hitch	
								Single Wrap	Double Wrap
									
Loading Factors		1	0.8	2	1.73	1.41	1	1.38	1.38
Lifting Capacity		**Vertical WLL**	**Choke WLL**	**Basket WLL**	**60º WLL**	**90º WLL**	**120º WLL**	**0º to 45º WLL**	**0º to 60º WLL**
KG	**Colour**								
1,000	Violet	1.0	0.8	2.0	1.7	1.4	1.0	1.3	1.3
2,000	Green	2.0	1.6	4.0	3.4	2.8	2.0	2.7	2.7
3,000	Yellow	3.0	2.4	6.0	5.1	4.2	3.0	4.1	4.1
4,000	Grey	4.0	3.2	8.0	6.9	5.6	4.0	5.5	5.5
5,000	Red	5.0	4.0	10.0	8.6	7.0	5.0	6.9	6.9
6,000	Brown	6.0	4.8	12.0	10.3	8.4	6.0	8.2	8.2
8,000	Blue	8.0	6.4	16.0	13.8	11.2	8.0	11.0	11.0
10,000	Orange	10.0	8.0	20.0	17.3	14.1	10.0	13.8	13.8
> 10,000	Orange	Marked WLL x LF							

* WLL is clearly marked on each sling.
* Colour coding on each sling added for safety.
* Protective sleeves are recommended for lifting sharp and rough cargo.
* Round Slings manufactured to AS4497-2018 – Safety Factor 7:1
* Flat Webbing Slings manufactured to AS 1353 Parts 1 & 2 1997 – Safety Factor 8:1.

Certex Lifting Pty Ltd is part of the Lifting Solutions Group in Australia, together with:

DYNAMIC RIGGING HIRE
LIFTING GEAR HIRE & SALES
STENHOUSE LIFTING & SAFETY SOLUTIONS
TOTAL LIFTING & RIGGING

Call us on **1800 CERTEX** or visit **certexlifting.com.au**
New South Wales • Queensland • South Australia • Victoria • Western Australia

LIFTING KNOW HOW